


Subdivision of T. 14 N., R. 68 E.

- Chains
- 20.80 Dim road, bears N. 20° W. and S. 20° E.
- 22.80 Top of short spur, slopes SW.; desc. 60 ft.
- 26.70 Ravine, course S. 70° W.; asc. 20 ft.
- 34.90 Top of spur, slopes SW.; desc. 30 ft.
- 37.60 Ravine, course S.; road, in bottom of ravine, bears N. 30° W. and S.; asc. 40 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



from which

A pinon pine, 5 ins. diam., bears N. 60 $\frac{1}{4}$ ° W., 189 lks. dist.; mkd.  $\frac{1}{4}$  S 6 BT.


A pinon pine, 6 ins. diam., bears S. 75°10' W., 178 lks. dist., mkd.  $\frac{1}{2}$  S 7 BT.

Asc. 255 ft. over a broken E. slope.

- 55.30 Top of spur, slopes S. 20° W.; desc. 155 ft. over W. slope.
- 64.70 Ravine, course S. 10° E.; asc. 260 ft. over rocky broken E. slope.
- 65.30 Trail, bears N. 10° W. and S. 10° E.
- 74.90 Top of ridge, bears N. and S.; desc. 10 ft.
- 77.58 Intersect the E. bdy. of T. 14 N., R. 67 E.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground to bedrock and in a mound of stone, for closing cor. of secs. 6 and 7, with brass cap mkd.



from which

The reestablished cor. of secs. 1 and 12, T. 14 N., R. 67 E., bears N. 0° 11' W., 3.61 chs. dist.

A juniper, 10 ins. diam., bears N. 17° E., 60 lks. dist., mkd. T 14 N R 68 E S 6 CC BT.

A pinon pine, 10 ins. diam., bears S. 74 $\frac{1}{2}$ ° E., 60 lks. dist., mkd. T 14 N R 68 E S 7 CC BT.

Land, mountainous.  
 Soil, sandy, shallow and coarse gravel, with considerable sliderock on surface.  
 Timber, pinon pine, juniper and mahogany.  
 Undergrowth, sagebrush, buckbrush and grass. Grazing, good.