

197

Dependent Resurvey, South Boundary, T. 15 N., R. 70 E.

Chains

dig pits, 18x18x12 ins. in each section, 3 ft. dist.

Land, rolling.
Soil, sandy clay.
No timber; undergrowth, sagebrush and greasewood.

S. 89° 51' E., bet. secs. 1 and 36.

Desc. 100 ft. over rolling land, on an E. slope, through scattering undergrowth, to the township corner.

40.07 Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

1/4 S 36
S 1

1942

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

80.14 The original cor. of Ts. 14 and 15 N., Rs. 70 and 71 E., which is monumented with a cottonwood post, 4 ins. square, 3 ft. long, lying upon remains of mound of earth and with dim illegible scribe marks.

At the corner point

Set an iron post, 3 ft. long, 3 ins. diam., 30 ins. in the ground, with the old wooden post deposited alongside, with brass cap mkd.

T15N
R70E R71E
S36|S31
S1|S6

T14N
1942

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, S. of cor.

Geographic position of this township corner is, latitude 39° 07' 12" N.; and longitude 114° 03' 21.5" W.

Elevation of this township corner, determined by direct tie to U.S.C.&G.S. bench mark X74 1934 is 5075 ft.

Land, rolling.
Soil, sandy clay.
No timber; undergrowth, sagebrush and greasewood.

Survey of a Portion of the East Boundary of T. 15 N., R. 70 E.

From the cor. of Ts. 14 and 15 N., Rs. 70 and 71 E.

North, bet. secs. 31 and 36.

Desc. 20 ft. over rolling land, along an even E. slope, through scattering undergrowth, to the next section corner.

40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.