

Survey of a Portion of the Subdivision of T. 15 N., R. 70 E.

Chains

76.61

Intersect the E. bdy. of sec. 24, T. 15 N., R. 69 E., on the W. bdy. of the Tp., at point for closing cor. of secs. 19 and 30.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T15N  
R69E R70E  
S24 | S19 CC  
     | S30  
1942

raise a mound of stone, 2 ft. base, 1½ ft. high, E. of cor.

From this point, the E. ¼ sec. cor. of sec. 24, bears South, 3.82 chs. dist., monumented with an iron post, 1 in. diam., 20 ins. above ground, in a mound of stone, and mkd. as described in the official record of the 1920 survey of the E. bdy. of T. 15 N., R. 69 E.

Land, rolling mountainous.  
Soil, rocky, gravelly clay.  
No timber; undergrowth, greasewood.

At the point for the W. ¼ sec. cor. of sec. 30, at midpoint on the W. bdy. of the section.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with brass cap mkd.

¼  
|  
S 30  
1942

raise a mound of stone, 2 ft. base, 1½ ft. high, E. of cor.

From this corner, the cor. of secs. 24 and 25, T. 15 N., R. 69 E., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1920 survey of the E. bdy. of T. 15 N., R. 69 E., bears South, 3.81 chs. dist.

From the cor. of secs. 19, 20, 29 and 30.

N. 0° 03' W., bet. secs. 19 and 20.

Asc. 40 ft. over mountainous land, on a SE. slope, through scattering undergrowth.

- 4.40 Spur, slopes SE.; desc. slightly over broken land.
- 6.60 Draw, drains SE.; asc. 30 ft. over a SW. slope.
- 10.60 Spur, slopes SW.; desc. 20 ft. over a NW. slope.
- 15.60 Draw, drains SW.; asc. 100 ft. over a SE. slope.
- 23.70 Spur, slopes SW.; desc. 10 ft. over a NW. slope.
- 27.90 Draw, drains SE.; asc. 10 ft. over a SW. slope.
- 31.00 Spur, slopes SE.; desc. 30 ft. over a NE. slope.