

Dependent Resurvey of the West Boundary of T. 7 N., R. 60 E.

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T7N
R59E R60E
| S 6
| S 7
1953

from which

A juniper, 8 ins. diam., bears N. $62\frac{1}{4}^{\circ}$ E., 198 lks. dist. mkd. S6 BT.

Dig a trench, 6 ft. diam., and raise a mound of earth and stone, 3 ft. diam., around corner. Bury the old mkd. limestone alongside and N. of the iron post.

Land, rolling.

Soil, gravelly clay loam.

Timber, scattering juniper; undergrowth, sagebrush.

N. 0° 11' E., along the W. bdy. of sec. 6.

Over low hills, draining generally SE.

17.60 Small wash, winding, course SE.

38.20 Wash, 25 lks. wide, 4 ft. deep, winding, course SE.

39.92 The $\frac{1}{4}$ sec. cor. of sec. 6, marked by a limestone, $8 \times 8 \times 4$ ins. above ground, mkd. $\frac{1}{4}$ on E. face, firmly set in a mound of stone, 3 ft. base, 1 ft. high.

At the corner point

Set an iron post, 30 ins. long, 2 ins. diam., 18 ins. in the ground, with the marked stone along E. side, with brass cap mkd.

| $\frac{1}{4}$ S6
1953

raise a mound of stone, 3 ft. base, around corner. Bury the old marked limestone alongside the iron post.

N. 0° 28' E., beginning new measurement.

Ascend 40 ft. over low hills.

7.50 Small spur, projects S. 50° E.

12.80 Ravine, 3 lks. wide, 1 ft. deep, course SE.

23.50 Side wash, 1 lks. wide, 6 ins. deep, course S. 60° E., begin ascent of SE. slope.

38.10 Top of rock outcrop, 40 ft. high, bears NE. and SW.; ascend slightly.

40.22 The cor. of Ts. 7 and 8 N., Rs. 59 and 60 E., marked by a quartzite $24 \times 8 \times 8$ ins., with three faint notches visible on one edge, loosely set in a mound of stone, 3 ft. diam., 1 ft. high.

At the corner point