		Portion of the Boundaries, T. 8 N., R. 61 E.
	Chains	The south, west and north boundaries of the township were surveyed by E. B. Monroe, Deputy Surveyor, in 1871.
		The following field notes are those of a retracement of the west two miles of the south boundary and of the west two miles of the north boundary, with remonumentation of identified original corner positions, only, and dependent resurvey of the west boundary.
		For description of instrumental equipment, Polaris observation, and method of determination of distances and directions, see field notes of the retracement and dependent resurvey of the boundaries of T. 7 N., R. 60 E., executed concurrently under this same survey group.
		The geographic position of the SW. corner of the township, determined from the official Bureau of Land Management map of Nevada, is latitude 38° 30' 30" N., and longitude 115° 10' 30" W.
		Portion of the South Boundary, T. 8 N., R. 61 E.
		Retracement and reestablishment of identified original corner positions only, on the W. 2 miles of the S. Bdy. of T. 8 N., R. 61 E., surveyed by E. B. Monroe, Deputy Surveyor, in 1871.
		The cor. of secs. 4, 5, 32 and 33, Ts. 7 and 8 N., R. 61 E. is marked by a juniper post, 2 ins. square, 3 ft. long, mkd. TVIIN RLXIE SIV on one face, SV on an adjacent face, illegible marks on other two faces, fallen on an old mound of earth between very faint evidence of pits.
		At the corner point
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.
		T8N R61E <u>S32 S33</u> S5 S4
•		T7N 1953
		Dig a trench, 6 ft. diam., and raise a mound of earth around corner. Bury the old juniper post alongside and W. of the iron post.
		S. 89° 28' W., bet. secs. 5 and 32.
		Over nearly level land.
	41.335	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original $\frac{1}{4}$ sec. cor. Corner not remonumented.
-	58.00	Rut road, winding, bears N. $60^{\circ}$ E. and S. $30^{\circ}$ W.
	82.67	The cor. of secs. 5, 6, 31 and 32, marked by the remains of the juniper post buried in the ground. The top portion, fallen nearby, is marked TVIIN RLXIE SV on one face with illegible scribe marks on other faces.
		At the corner point
-		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

U. S. GOVERNMENT PRINTING OFFICE

16-28520-1