

Dependant Resurvey, West Bdy., T. 9 N., R. 61 E.

Chains		Chains
64.60	Rut road, bears E. and W.	
70.50	Graded road, bears N. 48° E. and S. 46° W. to Gubler windmill; set a fence post with cruiser tag.	
80.20	The cor. of Ts. 9 and 10 N., Rs. 60 and 61 E., marked by a juniper post, 2x2 ins., 2 ft. long, firmly set in the ground and marked TXN RLXIE SXXXI on NE., TXN RLXE SXXXVI on NW., and with illegible marks on SE. and SW. sides, firmly set in the ground. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. T 10 N R 60 E R 61 E S 36 S 31 S 1 S 6 T 9 N 1953 Dig a trench, 5 ft. diam., and raise a mound of earth, 3 ft. diam., around corner. Reset the old juniper post and a new juniper post, 8 ft. long, alongside the iron post. From this corner Clark Windmill bears N. 18° 17' W. Water tank, bears N. 61° 09' W. Gubler Windmill bears S. 40° W. Land, nearly level. Soil, sandy clay. No timber; undergrowth, sagebrush.	
	North Bdy., T. 9 N., R. 61 E.	
	Retracement and Partial Dependent Resurvey of the Survey Executed by E. B. Monroe, Deputy Surveyor, in 1871. The cor. of Ts. 9 and 10 N., Rs. 61 and 62 E. is marked by the top part of a juniper post, 2 ins. square, 16 ins. long, mkd. TXN RLXIE SXXXI on one side, TXN RLXIE SXXXVI on a second side, with illegible marks on other two sides, lying on an old embedded mound of stone, 3 ft. diam., 6 ins. high. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T 10 N R 61 E R 62 E S 36 S 31 S 1 S 6 T 9 N 1953 Raise a mound of stone, 3 ft. diam., 7 ins. high, around corner. Reset the old juniper post alongside the iron post.	