

Dependent Resurvey, West Boundary, T. 10 N., R. 61 E.

Chains

For a description of instrumental equipment, Polaris observation, and method of determination of distances and directions. see field notes of the retracement and dependent resurvey of the boundaries of T. 7 N., R. 60 E., executed concurrently under this same group.

The geographic position of the SW. corner of the township, determined from the official Bureau of Land Management map of Nevada is latitude 38° 40' 45" N. and longitude 115° 10' 30" W.

Dependent Resurvey, West Boundary, T. 10 N., R. 61 E.

Reestablishment of the Survey Executed by
E. B. Monroe, Deputy Surveyor, in 1871.

Although originally surveyed as a common boundary, the corners on this boundary will not serve as corners for R. 60 E., therefore the monuments at all recovered, restored or reestablished corners are marked for R. 61 E., only.

From the cor. of Ts. 9 and 10 N., Rs. 60 and 61 E., described in the field notes of the dependent resurvey of the west boundary of T. 9 N., R. 61 E.

N. 0° 15' W., along the W. bdy. of sec. 31.

Over nearly level land.

39.78

Point for the $\frac{1}{4}$ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 31
1953

Dig a trench, 5 ft. diam., and raise a mound of earth, 3 ft. diam., around corner.

79.56

Point for the cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 10 N
R 60 E R 61 E
 | S 30
 | S 31
1953

Dig a trench, 5 ft. diam., and raise a mound of earth, 3 ft. diam., around corner.

From this corner

Clark Windmill bears N. 27° 40' W.
Government Well Tank bears S. 55° 06' W.

Land, nearly level.

Soil, clay.

No timber; undergrowth, sagebrush.