

Ind. Res. of the E. Bdy., T. 15 N., R. 59 E., with addition of Survey C. Cors.
for W. Bdy. of T. 15 N., R. 60 E.; Indep. Res. of E. Bdy., T. 15 N., R. 60 E.

Chains

The east boundary of T. 15 N., R. 59 E. and the east boundary of T. 15 N., R. 60 E. were originally surveyed by E. B. Monroe, Deputy Surveyor, in 1884. The south boundary of T. 16 N., R. 60 E. along the Third Standard Parallel North was originally surveyed by E. B. Monroe, Deputy Surveyor, in 1869, and independently resurveyed under Group 278, Nevada. The south boundary of the township was originally surveyed by E. B. Monroe, Deputy Surveyor, in 1884 and independently resurveyed under the present Group 277.

For a description of instrumental equipment used and their tests and adjustments, methods of determination of meridian, line measurement, etc., see the field notes of the survey of T. 14 N., R. 61 E. executed under the present Group 277, Nevada.

The geographic position of the southeast corner of T. 15 N., R. 60 E., determined by reduction of township exterior traverse from the cor. of Ts. 13 and 14 N., Rs. 59 and 60 E., which in turn is shown on U.S.G.S. quadrangle sheet "Treasure Hill" is latitude $39^{\circ} 06' 50''$ N., and longitude $115^{\circ} 10' 04''$ W.

Indep. Res., E. Bdy., T. 15 N., R. 59 E., with addition of Survey C. Cors. for W. Bdy., T. 15 N., R. 60 E.

Superseding the Survey Executed by E. B. Monroe,
Deputy Surveyor, in 1884.

Note: Diligent search along this line failed to reveal any evidence of any original corners.

From the cor. of Ts. 14 and 15 N., R. 59 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the Dependent Resurvey of the E. Bdy. of T. 14 N., R. 59 E.

North, on the E. bdy. of sec. 36, T. 15 N., R. 59 E.

Over rolling mountainous land, through scattering timber and undergrowth; desc. 80 ft. over NW. slope.

- 6.40 Wash, 10 lks. wide, 2 ft. deep, drains N. 70° E. for 10 chains, then turns to NE.; asc. 95 ft. over SE. slope.
- 7.60 Dirt road, bears N. 60° E. and S. 60° W.
- 12.57 The $\frac{1}{16}$ sec. cor. of sec. 6, T. 14 N., R. 60 E., described in the field notes of the subdivision of that township.
- 13.00 Spur, slopes N. 75° E.
- 13.80 Wash, 10 lks. wide, 2 ft. deep, drains E.
- 14.70 Small spur, slopes S. 80° E.
- 19.15 The closing cor. of Ts. 14 and 15 N., R. 60 E., described in the field notes of the Ind. Res. of the N. bdy. of T. 14 N., R. 60 E.
- 19.65 Wash, 10 lks. wide, 2 ft. deep, drains NE. from W.; asc. 135 ft. over SE. slope.
- 32.15 Spur, slopes N. 75° E.; desc. 255 ft. over N. slope to wash.
- 40.00 Point for the E. $\frac{1}{4}$ sec. cor. of sec. 36.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock, with brass cap mkd.