

Survey of the Subdivision of T. 14 N., R. 61 E.

Chains	Raise a mound of stone, $3\frac{1}{2}$ ft. base, 8 ins. high, around the iron post. Corner is on a low ridge which bears N. 15° E. and S. 15° W. Asc. 15 ft. along W. slope. 47.00 Ridge, bears S. 20° W. and N. 20° E.; desc. 35 ft. over NW. slope. 64.05 Draw, 20 lks. wide, 2 ft. deep, drains NW. Dirt road along bed of draw. Asc. 25 ft. over SW. slope. 74.85 Spur, slopes W. Thence along W. slope. 80.00 Point for the 1/16 sec. cor. of secs. 2 and 3. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd. 1/16 S 3 S 2 80 1953 from which A juniper, 6 ins. diam., bears S. 73° E., 161 lks. dist., mkd. BT. A juniper, 6 ins. diam., bears S. $41\frac{1}{2}^{\circ}$ W., 107 lks. dist., mkd. 1/16 S3 BT. Raise a flat mound of stone, 2 ft. diam., around the iron post. 86.85 Intersect the S. bdy. of sec. 35, T. 15 N., R. 61 E. Point for the closing corner of secs. 2 and 3. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to solid rock, with brass cap mkd. T15N R61E S35 S3 S2 CC T14N R61E 1953 from which A juniper, 8 ins. diam., bears S. $27\frac{1}{2}^{\circ}$ E., 192 lks. dist., mkd. S2 BT. A juniper, 7 ins. diam., bears S. $49\frac{1}{2}^{\circ}$ W., 151 lks. dist., mkd. T14N R61E S3 CC BT. The cor. of secs. 34 and 35, T. 15 N., R. 61 E., bears West, 2.26 chs. dist. Raise a mound of stone, 2 ft. diam., 15 ins. high, around the iron post. Land, rolling. Soil, gravelly to rocky. Timber, scattering juniper and pinon; undergrowth, rabbit brush, black brush and sagebrush.
--------	---