

Dependent Resurvey, Third Standard Parallel North, through R. 61 E.

Chains

23.70

Spur, slopes N.; desc. 145 ft. over W. slope.

39.68

The original standard corner of secs. 31 and 32, monumented with a limestone, 20x10x8 ins., firmly set in a mound of stone, mkd. with 5 notches on east and 1 notch on west face.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, with brass cap mkd.

S C
T16N R61E.
S31 | S32
1953

from which

A juniper, 8 ins. diam., bears N. 24° W., 47 lks. dist., mkd. S31 SC BT.

A juniper, 10 ins. diam., bears N. 17° E., 108 lks. dist., mkd. S32 SC BT.

Bury the old stone alongside and raise a mound of stone, 3 ft. base, 20 ins. high, around the iron post.

Land, rolling to broken.

Soil, sandy and gravelly to rocky.

Timber, pinon and juniper; undergrowth, sagebrush, rabbit brush and black brush.

N. $89^{\circ} 00'$ W., on the S. bdy. of sec. 31.

Over rolling to broken land, through heavy timber and undergrowth; desc. 125 ft. over broken W. slope.

8.30

Wash, 10 lks. wide, 4 ft. deep, drains S. 10° E.

8.65

Dirt road, bears NW. and S.; asc. 295 ft. over SE. slope.

28.85

Spur, slopes S. 1.30 chs., then turns to SW.; desc. 210 ft. over SW. slope.

39.78

Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
 $\frac{1}{4}$ S 31
1953

from which

A juniper, 4 ins. diam., bears N. 62° W., 18 lks. dist., mkd. $\frac{1}{4}$ S31 SC BT.

A juniper, 4 ins. diam., bears N. $28\frac{1}{4}^{\circ}$ E., 71 lks. dist., mkd. SC BT.