

Dep. Res. E. Bdy., T. 18 N., R. 59 E.; ~~XXXXXX XXXX XXXX XXXX XXXX XXXX XXXX XXXX XXXX~~ Indep. Res. W. Bdy., T. 18 N., R. 60 E.

Chains

T 19 N
R59E | R60E
S36 | S31
S1 | S6
T 18 N
1953

from which

A juniper, 7 ins. diam., bears S. 51° W., 69 lks. dist., mkd. S1 BT.

A juniper, 10 ins. diam., bears S. 31¼° E., 83 lks. dist., mkd. T18N R60E S6 BT.

A juniper, 6 ins. diam., bears N. 82½° E., 112 lks. dist., mkd. S31 BT.

A juniper, 14 ins. diam., bears N. 48¼° W., 66 lks. dist., mkd. T19N R59E S36 BT.

Land, nearly level.

Soil, clay loam to gravelly.

Timber, scattering juniper; undergrowth, black brush, rabbit brush, sagebrush, and some greasewood and shadscale.

~~XXXXXXXXXXXXXXXXXXXX~~ Independent Resurvey, East Boundary, T. 18 N., R. 60 E.

Establishment of ~~independent resurvey~~ corners along the E. bdy. of T. 18 N., R. 60 E. at intervals of 40.00' and 80.00 chs. of northing, counting from the SE. cor. of the township; and altering the common corners established by independent resurvey procedure along this line by W. H. Good, Cadastral Engineer, under Group 74 in 1922, to now refer to sections of T. 18 N., R. 61 E. only.

The cor. of Ts. 17 and 18 N., Rs. 60 and 61 E. is monumented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record of the 1922 Group 74 surveys of T. 18 N., R. 61 E. We efface the markings from bearing trees in T. 17 N. and alter the markings on the brass cap so that it now reads

T18N
R60E | R61E
S36 | S31
S 6
T17N R60E
1922

North, on the E. bdy. of sec. 36, T. 18 N., R. 60 E.

Note: See field notes of the 1922 independent resurvey of this line for items of topography, land descriptions, etc.

40.00

Point for the E. ¼ sec. cor. of sec. 36.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a limestone, 9x8x3 ins., mkd. with a cross (X), deposited at the base, and in a mound of stone to top, with brass cap mkd.

¼ S 36 |
1945