

~~XXXXXXXXXXXXXXXXXXXX~~  
 Independent Resurvey, East Boundary, T. 18 N., R. 60 E.

Chains

S 1  $\frac{1}{8}$  |  
 1945

from which

A pinon, 4 ins. diam., bears S. 15 3/4° W., 136 lks. dist.,  
 mkd. LC 8 S1 BT.

A pinon, 6 ins. diam., bears N. 56° W., 34 lks. dist.,  
 mkd. LC 1 S1 BT.

92.81

The cor. of Ts. 18 and 19 N., Rs. 60 and 61 E., which is monumented  
 with an iron post, 3 ins. diam., firmly set, mkd. and witnessed  
 as described in the official record.

Independent Resurvey, South Boundary, T. 18 N., R. 60 E.

Superseding the Survey Executed By  
 E. B. Monroe, Deputy Surveyor, in 1869.

From the cor. of Ts. 18 N., Rs. 60 and 61 E.

West, along the S. bdy. of sec. 36.

Over mountainous land, through scattering timber and dense  
 undergrowth; asc. 70 ft. along a SE. slope.

4.50

Spur, slopes S. 20° W.; desc. 250 ft. over W. slope.

15.20

Wash, 20 lks. wide, 2 ft. deep, course S. 60° W.; asc. 30 ft.  
 over S. slope.

17.40

Spur, slopes SW.; desc. 250 ft. over a W. to SW. slope.

37.20

Wash, 10 lks. wide, 1 1/2 ft. deep, course S. 20° W.; asc. 5 ft.

39.00

Low spur, slopes S. 15° W.; desc.

40.00

Point for the S. 1/4 sec. cor. of sec. 36.

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the  
 ground to bedrock, and in a mound of stone to top, with brass  
 cap mkd.

1/4 S 36

1945

Accessories impractical.

Desc. 60 ft. over a rolling S. slope.

61.60

Wash, 15 lks. wide, 1 1/2 ft. deep, course S. 10° W.; desc. 15 ft.

69.30

Wash, 12 lks. wide, 2 ft. deep, course S. 10° W.; desc. 20 ft.  
 along a general SW. slope.

80.00

Point for the cor. of secs. 35 and 36.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the  
 ground, with brass cap mkd.