

## Survey of the Subdivision, T. 20 N., R. 60 E.

Chains

87.83

Intersect the Fourth Standard Parallel North.

Point for the closing cor. of secs. 5 and 6.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T21N R60E  
 S31  
 S 6 | S 5  
 T20N R60E  
 C C  
 1958

Deposit broken glass at base of iron post.

Raise a mound of stone to S. of post.

From this intersection the standard ¼ sec. cor. of sec. 31, T. 21 N., R. 60 E. bears S. 89° 59' W., 11.94 chs. dist.

Land, rolling mountain slopes.

Soil, rocky clay loam.

Timber, juniper and pinon.

Undergrowth, sagebrush, bitter brush, weeds and grass.

At midpoint on the N. bdy. of sec. 5, point for the ¼ sec. cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

¼ S 5  
 T20N R60E  
 1958

Deposit broken glass at base of iron post.

From this point the standard cor. of secs. 31 and 32, T. 21 N., R. 60 E. bears S. 89° 59' W., 12.08 chs. dist. previously described.

At a point on the N. bdy. of sec. 6, 40.00 chs. W. in departure from the closing cor. of secs. 5 and 6.

Point for the ¼ sec. cor. of sec. 6.

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

¼ S 6  
 T20N R60E  
 1958

Deposit broken glass at base of iron post.

From this point the standard cor. of T. 21 N., Rs. 59 and 60 E. bears S. 89° 59' W., 11.89 chs. dist., previously described.

## General Description

The land in this survey consists mainly of rolling mountainous land at an elevation of approx. 6000 ft. above sea level. A narrow