

Dependent Resurvey of a Portion of the S. Bdy., T. 22 N., R. 55 E.

Chains

39.99

The original $\frac{1}{4}$ sec. cor. of secs. 3 and 34, which is monumented with a cedar post, 3 ins. square, 36 ins. above ground, marked with indistinct scribe markings.

At the cor. point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ $\frac{S34}{S3}$

1941

Reset the old wooden post, alongside the iron post and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

N. $89^{\circ} 46'$ W., beginning new measurement.

8.10

Road, bears N. and S.

8.30

Road, bears N. and S.

15.10

Leave nearly level land, asc. 60 ft. over an E. slope.

32.50

Road, bears N. 35° W. and S. 35° E.

40.07

The point for the original cor. of secs. 3, 4, 33 and 34; center of an old mound of stone, 3 ft. base; no marked post.

At the cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T22N R55E
 $\frac{S33}{S4}$ | $\frac{S34}{S3}$

T21N

1941

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, nearly level and rolling.

Soil, rocky and sandy clay.

No timber; undergrowth, sagebrush.

Survey of a Portion of the S. Bdy., T. 22 N., R. 55 E.

From the cor. of secs. 3, 4, 33 and 34.

West, bet. secs. 4 and 33.

Asc. 630 ft. over mountainous land, on an E. slope, through scattering undergrowth.

38.80

Spur, slopes S.; asc. 120 ft. over E. slope.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 33:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ $\frac{S33}{S4}$

1941