

DEPENDENT RESURVEY, E. BDY., T. 5 S., R. 68 E.

Chains

A juniper, 8 ins. diam., bears S. $39\frac{1}{4}^{\circ}$ W., 28 lks. dist.,
mkd. $\frac{1}{4}$ S1 BT.

A juniper, 10 ins. diam., bears N. $36\frac{1}{4}^{\circ}$ W., $85\frac{1}{2}$ lks. dist.,
mkd. $\frac{1}{4}$ S1 BT.

40.04 Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on surface rock
in crevice on E. side of rock outcrop, with a mound of stone
3 ft. diam., around E. side of post, rock outcrop on W. side,
to top, for a reference monument, with brass cap mkd.

$\frac{1}{4}$ Y
S 1
R M

1953

40.34 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, now altered to refer to sec. 6
only, marked by the original monument, a sandstone, 16 x 10 x 6
ins., mkd. $\frac{1}{4}$ on W. face, set in a small mound of stone, from
which, the original bearing trees:

A juniper, 10 ins. diam., bears S. $49\frac{1}{2}^{\circ}$ E., 39 lks. dist.,
with completely overgrown blaze on NW. side. Add the
marks "BT" on a new blaze.

A juniper, 8 ins. diam., bears N. $65\frac{1}{2}^{\circ}$ W., 16 lks. dist.,
mkd. $\frac{1}{4}$ S1 BT.

At the corner point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the
ground, and in a mound of stone, 2 ft. diam., to top, with brass
cap mkd.

$\frac{1}{4}$ S 6

1953

from which, a new bearing tree,

A juniper, 6 ins. diam., bears N. $57-3\frac{1}{4}^{\circ}$ E., 67 lks. dist.,
mkd. $\frac{1}{4}$ S6 BT.

N. $0^{\circ}10'$ W., bet. secs. 1 and 6. N. $\frac{1}{2}$ mile, beginning new measurement.

Ascend slightly.

2.10 Descend 70 ft.

13.40 Wash, 15 lks. wide, 1 ft. deep, course S. 20° E.; ascend 50 ft.

20.50 Descend 20 ft.

28.10 Head of ravine, course SE.; ascend 30 ft.

33.00 Crest of ascent.

38.90 Small wash, course W.

39.06 The original closing corner of T. 5 S., Rs. 68 and 69 E., marked
by a granite stone 20 x 12 x 8 ins., mkd. with 6 grooves on the
S., E. and W. faces and CC on S. face, set in a small mound of
stone. Remove the marks CC; add the marks WP on the S. face;