Chains

and reset the stone 10 ins. in the ground and in a mound of stone, from which the original bearing tree:

A juniper, 14 ins. diam., bears S.34-3/4.0W., 90 lks. dist., mkd. T5S R68E S1 CC BT.

39.12

Intersect the First Standard Parallel South, on S. bdy. of sec. 36, T. 4 S., R. 68 E.

Point for the closing cor. of T: 5 S., Rs. 68 and 69 E.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a mound of stone, $2\frac{1}{2}$ ft. diam. to top, with brass cap mkd.

T4S R6SE 536 S1 S6 R6SE R69E T5S . CC 1953

from which

A juniper, 10 ins. diam., bears S.28°E., 80 lks. dist., mkd. T5S R69E S6 CC BT.

The original bearing tree, bears S. 32 20 W., 96 lks. dist.

From the closing corner, the standard cor. of %.4S., Rs. 68 and 69 E., bears N.89°50'E., 32.40 chs. dist., and the standard sec. cor. of sec. 36 bears S.89°50'W., 7.44 chs. dist.

Land, rough, broken.
Soil, rocky.
Timber, juniper and pinon.

Dependent Resurvey of the First Standard Parallel South along the South Boundary of T. 4 S., through R. 68 E.

Reestablishment of the survey executed by H. B. Maxson, Deputy Surveyor, in 1901.

The standard corner of T. 4 S., Rs. 68 and 69 E. is marked by the original corner monument a basalt stone, 16x8x8 ins., mkd. with 6 notches on N., E. and W. edges, and set in a small mound of stone.

from which, the original bearing trees:

A juniper, 10 ins. diam.; bears N.60½°E., 32 lks. dist.; mkd. T4S R69E S31 BT.

A pinon, 14 ins. diam., bears N.6720W., 64 lks. dist., mkd. T4S.R68 S36 BT.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a mound of stone, 4 ft. diam., 6 ins. high, with the original marked stone buried alongside, with brass cap mkd.