1st. STAN. PAR. S., S. BDY. T. 4 S., R. 68 E.

	Chains	
	34.00	Descend 40 ft.
	37.50	Wash, 3 lks. wide, 6 ins. deep, course N.
	39.48	The standard corner of T. 4 S., Rs. 67 and 68 E. established at the terminus of the independent resurvey of the E. bdy. of T. 4 S., R. 67 E., by Deputy Surveyor H. B. Maxson in 1901, marked by a granite stone 16x8x6 ins., mkd. with 6 grooves on E. and W. and SC on N. faces, set in a small mound of stone, from which the 1901 bearing trees:
	3.	A juniper, 10 ins. diam., bears N.562°W., 46 lks. dist., mkd. T4S R67E S36 BT.
		A dead pinon, 8 ins. diam., mkd. T4S R68E S31 BT is fallen to the NE. At the corner point Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with the 1901 mkd. stone buried along the N. side, and
		in a mound of stone, 3 ft. diam., 10 ins. high, with brass cap mkd.
		SC T4S R67E R68E S 36 S 31
		1953
		from which, a new bearing tree
		A juniper, 8 ins. diam., bears N.77°E., 95 lks. dist., mkd. T4S R68E S31 SC BT.
		Land, rolling and broken. Soil, gravelly and rocky. Timber, juniper and pinon.
	,	South Boundary of T. 5 S., R. 68 E., M.D.M., Nevada
1011		From the cor. of T. 5 S.; Rs. 68 and 69 E.
		West, along S. bdy. of sec. 36.
		Ascend slightly.
	2.00	Descend 30-ft.
	8.70	Wash, 5 lks. wide, 10 ins. deep, course N.; ascend 50 ft.
	15.50	Descend 80 ft.
	22.30	Wash, 40 lks. wide, 2 ft. deep, course irregularly N.; ascend 20 ft.
	34.70	Side wash, 5 lks. wide, 30 ins. deep from SW., course N.80°E., ascend 120 ft.
	40.00	Point for the \frac{1}{4} sec. cor. of sec. 36.
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground and in a small mound of stone, with brass cap mkd.