

SUBDIVISION OF A PORTION OF T. 5 S., R. 68 E.

Chains	
3.00	Spur, projects S.15°W.; continue to ascend 20 ft.
6.50	E. cor. of cabin at mouth of Little Springs Canyon bears S.41°55'W.; descend 40 ft.
9.50	Head of ravine, course S.75°W.; ascend slightly.
12.50	Spur, slopes W.; descend 30 ft.
14.40	Head of ravine, course W.; ascend 60 ft.
20.60	Ridge, bears SE. and NW.
25.60	Same ridge bears NE. and SW.; descend 30 ft.
33.30	Ravine course NW.
37.60	Saddle in same ridge, bears N.30°W. and SE.; descend slightly.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 2 $\frac{1}{4}$ ins. in the ground, with a collar of stone around the post, with brass cap mkd. $\frac{1}{4}$ S 2 S 1 1953 from which. A juniper, 8 ins. diam., bears S.54°E., 35 lks. dist., mkd. $\frac{1}{4}$ S1 BT. A pinon, 5 ins. diam., bears N.33 $\frac{1}{2}$ °W., 27 lks. dist., mkd. $\frac{1}{4}$ S2 BT. Ascend 70 ft.
55.00	Spur, slopes SE.; descend 325 ft.
74.60	Ravine course NW.; ascend 160 ft.
79.68	Intersect the First Standard Parallel South. Point for the closing corner of secs. 1 and 2. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in the ground, and in a mound of stone, 4 ft. base, 10 ins. high, with brass cap mkd. T4S R68E S35 S2 S1 T5S R68E CC 1953 from which A juniper, 10 ins. diam., bears S.32°E., 31 lks. dist., mkd. S1 CC BT. A pinon, 12 ins. diam., bears S.12 $\frac{1}{2}$ °W., 85 lks. dist., mkd. S2 CC BT.