

SUBDIVISION OF A PORTION OF T. 8 S., R. 68 E.,  
M.D.M., NEVADA

Chains

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.

N.89°53'W., bet. secs. 25 and 36, on sectional correction line.

Over broken and mountainous land, through scattered juniper and low undergrowth.

Desc. 220 ft. over SW. slope.

14.35 Wash, 20 lks. wide, 3 ft. deep, course SW. Ascend 65 ft.

15.75 Dirt road, bears S.50°W. and N.50°E.

21.55 Wash, 20 lks. wide, course SE.

31.75 Wash, 10 lks. wide, course SE.

36.00 Spur, slopes SW. Descend 50 ft. over W. slope.

40.16 Point for the  $\frac{1}{4}$  sec. cor. of secs. 25 and 36.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins. in the ground, to rock, with brass cap mkd.

$\frac{1}{4}$  S 25  
S 36  
1953

raise a flat mound of stone, 4 ft. base, 8 ins. high, around the iron post.

Ascend 25 ft.

45.30 Small spur, slopes SE. Descend 50 ft. over SW. slope.

49.40 Road, bears S.30°E. and N.35°W. / Ascend 245 ft. in wash draining S. 30° E.

67.00 Spur, slopes E. Descend 85 ft. over S. slope.

80.32 Point for the cor. of secs. 25, 26, 35 and 36.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 18 ins. in the ground, to bed rock, with brass cap mkd.

T8S R68E  
S 26 | S 25  
S 35 | S 36  
1953

Land, mountainous.

Soil, rocky.

Timber, juniper; undergrowth, buckbrush, cacti and oak.

The point for standard corner of secs. 35 and 36, T.8S., R.68E., is referenced by a witness corner monument N.89°35'W., 178 lks. dist., which is an iron post, 2 ins. diam., firmly set and marked as described in the 1934 resurvey record.

From the true point for corner