		For description and test of instruments and method of measurements refer to the field notes of T. & S., R. 68 E., executed under this same group. The directions of lines were initially determined by reference to adjacent surveys and verified at frequent intervals throughout the progress of the survey by Polaris and solar observations.
	ę	East Boundary of T. 6 S., R. 69, E., M.D.M.
	Chains -	From the cor. of Ts. 6 and 7 S., Rs. 69 and 70 E., described in the field notes of the W. bdy. of T. 7 S., R. 70 E., in latitude 37°22'30" N., longitude 114°12'50" W. North, bet. secs. 31 and 36.
		Descend 60 ft. over N. slope.
	2.20	Wash, 20 lks. wide, 2 ft. deep, course N.70°W.; ascend 280 ft. over broken SW. slope, over huge boulders and numerous rock outcrops.
	22.00	Spur, projects west approximately 5 chs. then N.70°W; descend 110 ft. over boulder strewn NW. slope.
	27.70	Ravine, course N.80°W.; ascend 90 ft. over broken SW. slope.
	35.10	Short side spur, slopes W.
	39.40	Side spur slopes N.70°W.
	140.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36.
		Set an iron post, 30 ins. long, 2 ins. diam., 2 ins. in the ground to bedrock and in a mound of stone, 5 ft. base, to top, with brass cap mkd.
		1 4
		s 36 s 31
		1953
		from which
		A fork of a pinon, 8 ins. diam., bears N.16°E., 47 1ks. dist., mkd. 4 S31 BT.
		A pinon, 8 ins. diam., bears S.584°W., 23 lks. dist., mkd. 4 S36 BT.
		Descend 25 ft.
•	42.00	Head of ravine, course N.70°W., changing to W. and to SW.; ascend 50 ft.
	50.20	A main spur, projects NW. from S.20°E.; descend 10 ft.
	54.30	Side spur, projects E.; desc. 240 ft.
	68.50	Recross branch of same spur, projects N.30°W.; a side spur projects N.20°E.; descend 100 feet.
	714.10	Shallow wash, 10 lks. wide, course NE.; ascend slightly.
	80.00	Point for the cor. of secs. 25, 30, 31 and 36.
		Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, with brass cap. mkd.