-		
		For description and test of instruments and method of measurements refer to the field notes of T.8S., R.68E., M.D.M., Nevada executed under this same group. The directions of lines were initially determined by reference to adjacent surveys and verified at frequent intervals throughout the progress of the survey by Polaris and solar observations.
		East Boundary of T. 7 S., R. 70 E., M.D.M., Nevada
	W The second sec	From the cor. of Ts. 7 and 8 S., Rs. 70 and 71 E., in latitude 37°17'16" N., longitude 114°06'19" W., described in the field notes of the E. bdy. of T. 8 S., R. 70 E., executed concurrently under Group No. 295. North, bet. secs. 31 and 36.
		Over rolling land, through low brush. Ascend 125 ft. over S. to SE. slope.
	20.00	Change of slope to E.; continue slight ascent.
	23.00	Descend 155 ft. over general E. to NE. slope.
	32.30	Wash, course SE. Ascend 70 ft.
	32.60	Old road, bears N.55°W. and SE.
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36.
		Set an iron post, 30 ins. long, 2 ins. diam., over cross (+) on bedrock, supported in a mound of stone, 5 ft. base, to top, with brass cap mkd.
		$\frac{1}{4}$
		s.36 s 31
	٠	00ze flat Reservoir #1 bears N.42°52'E., 71.40 chs. dist. Ascend slightly.
	41.00	Top.of knoll, on small spur, sloping to NH. Descend 35 ft.
	53.60	Stub road, bears N.30°E., to Ooze Flat reservoir.
		Ascend 170 ft. over gradual S. slope, through very scattered juniper.
	68.00	Knoll; descend 50 ft. over N. slope.
	80.00	Point for the cor. of secs. 25, 30, 31 and 36.
		Set an iron post, 30 ins. long, 2 ins. diam., 20 ins. in the ground, with brass cap mkd.
		T7S R70E R71E S 25 S 30 S 36 S 31 1953
-		raise a mound of stone, 3 ft. base, 10 ins. high, around iron post.
1	,	