

Chains

From the point for the township corner, the corner of secs. 1, 6, 7 and 12 on the E. bdy. of T. 16 N., R. 62 E. bears S. 0°56'W., 80.68 chs. dist., a mound of stone recovered from ties recorded in Mineral Survey No. 2812. Ties check exactly.

Set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground to underlying rock and in a mound of stone to top, for cor. of secs. 1, 6, 7 and 12, with brass cap mkd.

T16N
R62E R63E
S 1 | S 6
S12 | S 7
1939

from which

A pine, 12 ins. diam., bears N. 23° E., 36 lks. dist.,
mkd. T16N R63E S6 BT

A pine, 5 ins. diam., bears S. 10° E., 489 lks. dist.,
mkd. T16N R63E S7 BT

A pine, 4 ins. diam., bears S. 17 3/4° W., 80 lks. dist.,
mkd. T16N R62E S12 BT

A pine, 6 ins. diam., bears N. 81 1/2° W., 148 lks. dist.,
mkd. T16N R62E S1 BT.

From the point for the township corner, the cor. of secs. 31, 32, 5 and 6, on the S. bdy. of T. 17 N., R. 63 E., bears N. 89°02' E., 77.99 chs. dist.; a limestone 3x10x20 ins., mkd. with 5 grooves on E. face, 1 groove on W. face, set in a mound of stone and earth.

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to underlying rock and in a mound of stone to top, with the original stone at base, for cor. of secs. 5, 6, 31 and 32 with brass cap mkd.

T17N R63E
S31 | S32
S 6 | S 5
T16N
1939

from which

A pine, 8 ins. diam., bears N. 73° E., 171 lks. dist.,
mkd. T17N R63E S32 BT

A pine, 3 ins. diam., bears S. 53 1/2° E., 97 lks. dist.,
mkd. T16N R63E S5 BT

A pine, 5 ins. diam., bears S. 58 3/4° W., 279 lks. dist.,
mkd. T16N R63E S6 BT

A pine, 10 ins. diam., bears N. 22° W., 324 lks. dist.,
mkd. T17N R63E S31 BT.

From the point for the Tp. cor.

N. 1° 02' E. bet. secs. 31 and 36; along east bdy. T. 17 N., R. 62E.

40.34 Proportionate point, no trace of the original 1/4 sec. cor.

80.68 Proportionate point, no trace of the original sec. cor.