23	DEPENDENT RESURVEY OF A PORTION OF WEST BOUNDARY, T. 44 N., R. 27 E.
Chains	
40.00	Point for $\frac{1}{4}$ sec. cor. of sec. 30, at record distance; there is no remaining evidence of the original corner.
	Set an iron post, 3 ft. long, 1 in. diam., 23 ins. in the ground, to bedrock, with a granite stone, 5x4x2 ins. mkd. with a cross (X) deposited at base, and in a mound of stone to top, with brass cap mkd.
,	1940
	No suitable accessory.
72.53	Point for the $\frac{1}{4}$ sec. cor. of sec. 24.
	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a granite stone, 6x4x2 ins. mkd. with a cross (X) deposited at base and in a mound of stone to top, with brass cap mkd.
	½ S 24
	1941
	No suitable accessory.
80.00	Point for cor. of secs. 19 and 30, at record distance; there is no remaining evidence of the original corner.
	Set an iron post, 3 ft. long. 2 ins. diam., 18 ins. in the ground, upon a cross (X) on bedrock, and in a mound of stone to top, with brass cap mkd.
	T44N T44N
	R26E S 19 S 24
	S 30 R27E
	1941
	No suitable accessory.
	Land, rolling.
	Soil, rocky clay, 3rd rate. No timber.
	Undergrowth, sagebrush. Grazing, poor.
	SURVEY OF A PORTION OF THE EAST BOUNDARY T. 44 N., R. 26 E.
	From the cor. of secs. 19 and 30, T. 44 N., R. 27 E.
	North, along the E. bdy. of sec. 24.
	Desc. 160 ft. over rough mountainous land on a N. slope. through scattering undergrowth.
2.00	Draw, drains NE.; asc. 680 ft. over a SE slope.
32.53	Point for cor. of secs. 13 and 24, at 160.00 chs. N. of SE. cor. of T. 44 N., R. 26 E.
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.