

Dependent Resurvey of a Portion of S. Bdy., T. 45 N., R. 26 E.

Chains

This resurvey was executed with Buff and Buff light mountain solar transit No. 9210, the property of the General Land Office. For description, date of approval and field tests of this instrument, together with tests of all minor equipment, see page 1. Dependent Resurvey of the 9th Stan. Par. N., S. Bdy. of T. 46 N., R. 26 E., this group.

The geographic position of the SE. cor. of T. 45 N., R. 26 E., is latitude $41^{\circ} 45' 45''$ N. and longitude $118^{\circ} 59' 00''$ W.

The bearings of all lines were determined by the solar transit method.

DEPENDENT RESURVEY OF PORTION OF S. BDY., T. 45 N., R. 26 E.

Reestablishment of the survey executed by G. W. Garside, U.S. Deputy Surveyor, in 1879.

NOTE: In this resurvey, no original corners were recovered to the East of the cor. of secs. 2, 3, 34 and 35. In the present survey corners are reestablished for sections of T. 45 N., R. 26 E. only.

The cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.; which is marked by a basalt stone, $16 \times 6 \times 4$ ins. above ground, firmly set, and mkd. with 4 notches on the W. edge and 6 notches on the N. face.

At cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited at base, for the cor. of secs. 34 and 35, T. 45 N., R. 26 E. only, with brass cap mkd.

T45N	R26E
S34	S35
1940	

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

East, along the S. bdy. of sec. 35.

Desc. 90 ft. over rolling land, on a broken SE. slope, through scattering undergrowth.

40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 35, at record distance.

Set an iron post, 3 ft. long, 1 in. diam., upon a cross (X) upon bedrock and with its entire length in a mound of stone, with brass cap mkd.

$\frac{1}{4}$	S 35
1940	

58.20 Winding draw, course N. 30° E.; asc. 40 ft. over a broken NW. slope.

79.60 Road, bears N. 70° E. and S. 70° W.

80.00 Point for the cor. of secs. 35 and 36, at record distance.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T45N	R26E
S 35	S 36
1940	

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.