

Portion of the N. Bdy. of T. 46 N., R. 28 E.

Chains	<p>N. 85° 52' E., bet. secs. 5 and 32.</p> <p>Over low rolling hills, through medium dense sagebrush.</p> <p>18.70 Unimproved road, on curve from N. 10° W. to S. 20° W.</p> <p>40.11 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32. at proportionate position; there is no remaining evidence of the original corner.</p> <p>Corner not reestablished.</p> <p>43.80 Draw, course S. 40° W.</p> <p>80.21 The cor. of secs. 4, 5, 32 and 33, which is monumented with a basalt stone, 18x12x10 ins. above ground, marked with 4 notches on E. edge and 2 notches on W. edge.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original corner monument deposited at the base, with brass cap marked</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td>T 47 N</td> <td>R 28 E</td> </tr> <tr> <td>S</td> <td>S 32</td> <td>S 33</td> </tr> <tr> <td>A</td> <td colspan="2" style="border-top: 1px solid black;">S 5 S 4</td> </tr> <tr> <td>R</td> <td colspan="2" style="border-top: 1px solid black;">1940</td> </tr> </table> <p>raise a mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, W. of cor.</p> <p>Land, low rolling hills. Soil, sandy, 2nd rate. No timber; undergrowth, sagebrush. Grazing, poor.</p>		T 47 N	R 28 E	S	S 32	S 33	A	S 5 S 4		R	1940	
	T 47 N	R 28 E											
S	S 32	S 33											
A	S 5 S 4												
R	1940												
	<p>Dependent Resurvey of the 4th Meridional Section Line of T. 46 N., R. 28 E., Delineating a Portion of the East Bdy. of the Charles Sheldon Antelope Range.</p> <p style="text-align: center;">Reestablishment of the Survey Executed by Hatch, Skinner and Preble, U.S. Deputy Surveyors, in 1874.</p> <p>From the standard corner of secs. 32 and 33 on the S. bdy. of the township, which is monumented with an iron post, 2 ins. diam., 6 ins. above ground, marked and witnessed as described in the field notes of the resurvey of a portion of the 9th Stan. Par. N., through a portion of Rs. 26, 27 and 28 E.</p> <p>N. 0° 03' W., bet. secs. 32 and 33.</p> <p>Over rolling land, through dense undergrowth.</p> <p>24.30 Road bears N. 89° W. and S. 89° E.</p> <p>41.12 Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with a quart of charcoal deposited at base, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>S</td> <td>$\frac{1}{4}$</td> </tr> <tr> <td>A</td> <td>S 32 S 33</td> </tr> <tr> <td>R</td> <td>1940</td> </tr> </table> <p>No suitable accessory.</p> <p>82.23 Point for the cor. of secs. 28, 29, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p>	S	$\frac{1}{4}$	A	S 32 S 33	R	1940						
S	$\frac{1}{4}$												
A	S 32 S 33												
R	1940												