

DEPENDENT RESURVEY
9TH STAN. PAR. N., S BDY. T. 46 N., R. 26 E.

Chains	
33.40	Road, bears N. 10° E. and S. 10° W.; along a draw, draining N. 10° E.; asc. 50 ft. over a W. slope.
40.00	Spur, slopes SW.; desc. 30 ft. over an E. slope.
50.50	Draw, drains N. 10° E.; asc. 90 ft. over a W. slope.
63.38	The standard cor. of secs. 35 and 36, which is monumented with a pumice stone, 24x12x4 ins., above ground, mkd. with 1 notch on the E. and 6 notches on the N. faces. At cor. point, Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited at base, with brass cap mkd. <div style="text-align: center;"> S A R S C T46N R26E S 35 S 36 <hr style="width: 50%; margin: 0 auto;"/> 1940 </div> raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor. Land, rolling mountainous. Soil, rocky, sandy, clay, 3rd rate. No timber; undergrowth, sagebrush. Grazing, fair.
	<p>Note: From the standard cor. of secs. 35 and 36, T. 46 N., R. 26 E., to the standard cor. of T. 46 N., Rs. 27 and 28 E., exhaustive investigation shows that original monuments on the standard line have been obliterated.</p> <p>S. 89° 08' E. along the S. bdy. of sec. 36.</p> <p>Asc. 40 ft. over rolling mountainous land on a W. slope, through scattering undergrowth.</p>
22.20	Top of ascent, bears N. and S.; desc. 140 ft. over an E. slope,
29.10	Draw, drains N. 10° E.; asc. 130 ft. abruptly.
34.60	Draw, drains N. 60° W.; asc. slightly over broken land.
41.00	Draw, drains N. 50° W.; asc. 150 ft. over a SW. slope.
43.36	Point for the standard ¼ sec. cor. of sec. 36, at proportionate distance. Set an iron post, 3 ft. long, 1 in. diam., upon a cross (X) on bedrock with its entire length in a mound of stone, with brass cap mkd. <div style="text-align: center;"> S A R S C ¼ S 36 <hr style="width: 50%; margin: 0 auto;"/> 1940 </div>
72.50	Top of ascent, bears N. and S.; desc. 80 ft. over an E. slope.
81.80	Draw, drains N.; asc. 40 ft. over a rocky W. slope.