

DEPENDENT RESURVEY OF W. BDY. OF T. 20 N., R. 19 E.

Chains  
40.24 Intersect the original  $\frac{1}{4}$  sec. cor., which is a trapstone, 7x9x20 ins., mkd.  $\frac{1}{4}$  on W. face, firmly set.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original corner stone deposited at the base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S 1 | S 6  
1941

raise a mound  
of stone, 4 ft. diam., 1 ft. high, around corner post.

Thence

N. 0°57' W., bet. secs. 1 and 6, (north half mile.)

Over rolling land,

8.90 Gully, drains NE. 1 ch., thence N.

23.70 Recross gully, drains NW.

30.00 Leave rolling land end enter nearly level plain, bears NE. and SW.; continue through very dense yellow top undergrowth.

The reestablished closing cor. of secs. 1 and 6 falls in center of east-west road where the corner monument may be disturbed. Therefore, at

40.59 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for witness closing cor. of secs. 1 and 6, T. 20 N., Rs. 18 and 19 E., with brass cap mkd.

WC  
T21N  
S 31  
-----  
S1 | S6  
R18E | R19E  
T20N  
CC  
1941

raise a circular  
mound of stones, 4 ft. base, 12 ins. high around corner post.

41.08 Intersect the Fourth Standard Parallel North at proportionate distance for the original closing cor. of T. 20 N., Rs. 18 and 19 E., where I had set an iron post, 2 ins. diam., as described in the resurvey of the S. bdy. of T. 21 N., R. 19 E., executed under this same group.

From this point,  
The std. cor. of T. 21 N., Rs. 18 and 19 E., bears S. 89°48' W., 15.55 chs. dist. and the std.  $\frac{1}{4}$  sec. cor. of sec. 31 bears N. 89°48' E., 24.47 chs. dist.

Land, rolling.  
Soil, sandy to fine gravelly clay loam, 3rd rate.  
Undergrowth, yellow top, sagebrush, wild peach, buck brush.  
Grazing, fair.

DEPENDENT RESURVEY OF PORTION OF SUBDIVISIONS OF T. 20 N., R. 19 E.

Reestablishment of surveys executed by Solomon W. Foreman in 1865 and by J. B. Menardi in 1905.