DEPENDENT RESURVEY OF SUBDIVISION OF T. 20 N., R. 19 E.

Chains	from which,
	A juniper, 6 ins. diam., bears N. 861°W., 284 lks. dist., mkd.
	$\frac{1}{4}$ S2 BT.
	A juniper, 6 ins. diam., bears S. $40\frac{1}{4}$ °E., 191 lks. dist., mkd. $\frac{1}{4}$ S11 BT.
*	Thence
	S. 88°511' W., bet. secs. 2 and 11, (west half mile.)
	Over gently rolling SW. slopes through very dense undergrowth and scattering small juniper timber.
5.40	Small surface drain, course SW.
40.09	The cor. of secs. 2, 3, 10 and 11.
	Land, rolling. Soil, shallow gravelly to rocky clay loam, 3rd and 4th rate. Undergrowth, sagebrush, buck brush. Grazing, good.
	N. 0°03' W., bet. secs. 2 and 3, (south half mile.)
	Over gentle S. slope through very dense undergrowth.
4.15	Road, bears N.20°E. and S.20°W.
17.50	Foot of hills, bears E. and S.70°W.; asc. 190 ft. over broken S. slope.
22.50	Small rocky knoll, along E. side.
40.04	Intersect the original $\frac{1}{4}$ sec. cor., which is a granite stone, $8x9x18$ ins., mkd. $\frac{1}{4}$ on W. face, firmly set and surrounded by a small embedded mound of stones.
	At point for cor.,
	Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground to solid rock, with the original corner stone deposited at the base, and in a large supporting mound of stones, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$
	s 3 s 2
	1941
	Thence
	N. 0°51' E., bet. secs. 2 and 3, (north half mile.)
1.30	Spur ridge, curves from N.20°E. to NW.; desc. 180 ft. over broken NW. slope of spur.
17.00	Gully, drains NW. from NE.; asc. 120 ft. over rocky SE. slope.
24.50	Rocky knoll; spur slopes E. 6 chs.
37.80	Rocky knoll, bears S. from NE.; desc. 15 ft. over rugged NW. slope.
38.86	Intersect the Fourth Std. Parallel North at the reestablished closing cor. of secs. 2 and 3, which is an iron post, 2 ins. diam., set, marked and witnessed as described in the field notes of the resurvey of the S. bdy. of T. 21 N., R. 19 E., executed under this group.