

344

DEPENDENT RESURVEY OF FOURTH STAN. PAR. NORTH THROUGH R. 19 E.

Chains
80.04

granite stone, 7x8x30 ins., mkd. 6 grooves on N., E. and W. faces, firmly set.

At point for cor.,

Set an iron post, 3 ft. long, 3 ins. diam., 30 ins. in the ground, with the original corner stone deposited at the base, for std. cor. of Ts. 21 N., Rs. 18 and 19 E., with brass cap mkd.

SC	
T21N	
R18E	R19E
S 36	S 31
1941	

raise a mound

of stone, 4 ft. base, 1½ ft. high, N. of cor.

Land, rolling.

Soil, shallow coarse gravelly clay loam, 3rd rate.

Undergrowth, sagebrush, yellow top, wild peach.

No timber.

Grazing, good.

DEPENDENT RESURVEY OF THE EAST BDY. OF T. 21 N., R. 19 E.

Reestablishment of surveys executed by A. J. Hatch in 1867. This line was resurveyed by J. B. Menardi in 1906.

From the std. cor. of T. 21 N., Rs. 19 and 20 E.,

N. 0°17' E., bet. secs. 31 and 36, (south half mile.)

Over broken hilly land through dense undergrowth and scattering scrub juniper; asc. 30 ft. over broken SE. slope.

7.50 Old mine road, unused, bears NW. and SE.

9.50 Spur, slopes E. from W.; along broken E. slope.

32.10 Recross spur ridge, bears S.60°W. and NE.; desc. along steep NW. slope.

39.90 Intersect the original ¼ sec. cor., which is a granite rock, 10x18 x30 ins., mkd. ¼ on W. face, firmly set in an old mound of stones.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original corner stone deposited at the base, for ¼ sec. cor., with brass cap mkd.

¼	
S36	S31
1942	

from which,

A juniper, 3 ins. diam., bears S.81-3/4°E., 51 lks. dist., mkd. ¼ S31 BT.

A juniper, 4 ins. diam., bears N.26½°W., 142 lks. dist., mkd. ¼ S36 BT.

Thence,

N. 0°12' E., bet. secs. 31 and 36, (north half mile.)

5.00 Low rocky spur, slopes N.10°W.; desc. 100 ft. over steep N. slope.