

DEPENDENT RESURVEY OF THE EAST BDY. OF T. 21 N.,R. 19 E.

Chains

40.20

Intersect the recovered point for the cor. of secs. 1 and 12 at record bearing and distance from the original bearing tree.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, in a mass of concrete, for cor. of secs. 1 and 12, with brass cap mkd.

T21N

R19E | R20E

S 1 |

S 12

S 6

1942

from which,

The original bearing tree:

A juniper, 10 ins. diam., bears S.54 $\frac{1}{4}$ °W., 148 lks. dist., mkd. T21N R20E S12 BT.

New bearing tree:

A juniper, 10 ins. diam., bears N.33°W., 118 lks. dist., mkd. T21N R19E S1 BT.

Land, rolling.
Soil, sandy, 3rd rate.
Undergrowth, sagebrush, buck brush, yellow top.
Timber, juniper.
Grazing, fair.

N. 0°31' E., along E. bdy. of sec. 1, (south half mile.)

Over rolling land through dense undergrowth and scattering timber.

4.10

Road, bears N.20°W. and S.20°E.

16.70

Recross same road, bears N.30°E. and S.30°W.

25.00

Desc. gentle N. slopes.

40.53

Intersect the original $\frac{1}{4}$ sec. cor., which is a granite rock, 4x7x17 ins., mkd. $\frac{1}{4}$ on W. face, firmly set.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original corner stone deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S 1 |

1942

from which,

Original bearing tree: