

Dependent Resurvey of the East Boundary, T. 14 N., R. 21 E.

Chains	
	Land, mountainous. Soil, stony clay; series of ledges and outcrops with loose boulders. Timber, pinon pine and juniper. Undergrowth, sagebrush, bitterbrush, gooseberries, mahogany and a scant stand of native grasses.
	N. 0° 22' E., bet. secs. 1 and 6. Over mountainous land, through dense timber and undergrowth; descend 30 ft. along NW. slope.
2.00	Head of draw, course NW.; descend 150 ft.
10.60	Cross same draw, course NE.; descend 121 ft.
21.50	Leave timber, bears N. 70° E. and W.; continue across a heavy dense sage flat.
27.70	A graded dirt road, bears N. 55° E. and SW.
30.00	Channel of ravine, 12 lks. wide, 4 ft. deep, with a trickling small intermittent stream, course N. 55° E.; thence across gullied bench land draining E. Enter scattering timber.
36.00	Low flat bench spur, slopes NE.
37.40	Channel of ravine 5 lks. wide, 1 ft. deep, course NE.
39.30	Channel of ravine, 7 lks. wide, 1 ft. deep, course E.; ascend 5 ft. along SE. slope.
39.90	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a circular collar of stone around iron post, with brass cap mkd. <div style="text-align: center;"> $\frac{1}{4}$ S 1 S 6 1950 </div>
	from which A pinon pine, 6 ins. diam., bears S. 70° E., 47 lks. dist., mkd. $\frac{1}{4}$ S6 BT. A juniper, 6 ins. diam., bears S. 61 $\frac{3}{4}$ ° W., 51 lks. dist., mkd. $\frac{1}{4}$ S1 BT.
51.00	Low spur, slopes E.; descend 25 ft. over NE. slope.
57.25	Drift wire fence bears N. 20° W. and S. 20° E. end in cutbank about 3.00 chs. NW.
58.00	Rim of eroded basin, bears NW. and SE.
61.50	Foot of clay cut bank, bears NE. and SW.; ascend 115 ft.
65.30	Top of clay spur, projects N. 75° E.; descend 186 ft.
68.00	Gully, course NE.
71.00	Spur, projects NE.