

Dependent Resurvey of the North Boundary, T. 14 N., R. 21 E.

Chains	
	S. $89^{\circ} 02'$ W., along the N. Bdy. of sec. 6.
	Desc. 180 ft. over a W. slope, through scattering scrub timber and dense undergrowth.
8.90	Ravine, course N. 10° W., ascend 220 ft. over a series of broken spurs and gulches along NE. slope to $\frac{1}{4}$ sec. cor.
14.40	Spur, projects NE.
17.90	Rocky ravine, 8 lks. wide, course N.
23.40	Top of flat spur, slopes NE.
29.00	Head of ravine, course NE.
32.40	Spur, slopes NE.
37.255	Top ridge, bears N. and S.
	Point for the $\frac{1}{4}$ sec. cor. of sec. 31, T. 15 N., R. 21 E. only, which is 440.00 chs. in departure from the SE. Tp. corner.
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	----- $\frac{1}{4}$ S 31 1950
	from which
	A pinon pine, 7 ins. diam., bears N. $47\frac{3}{4}^{\circ}$ E., 17 lks. dist., mkd. $\frac{1}{4}$ S31 BT.
	A pinon pine, 6 ins. diam., bears N. $68\frac{1}{2}^{\circ}$ W., 38 lks. dist., mkd. $\frac{1}{4}$ S31 BT.
41.00	Descend 91 ft. over W. slope. Side ravine, 10 lks. wide, course N. 20° W.; ascend 25 ft.
41.765	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. The function of this corner is now changed to refer to the $\frac{1}{4}$ sec. cor. of sec. 6, T. 14 N., R. 21 E. only.
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$ S 6 1950
	from which
	A pinon pine, 7 ins. diam., bears S. 57° E., 52 lks. dist., mkd. $\frac{1}{4}$ S6 BT.
	A pinon pine, 6 ins. diam., bears S. $28\frac{1}{2}^{\circ}$ W., 43 lks. dist., mkd. $\frac{1}{4}$ S6 BT.
47.40	Shoulder of spur, slopes N.; descend 116 ft. over a NW. slope
53.20	Ravine, 40 lks. wide, course N. 15° E.; ascend 70 ft.
53.50	Old trail road not used, bears N. 20° W. and S. 20° E.
58.00	Spur projects N. 50° E.; descend 343 ft. over a broken NW. slope.
80.10	A graded mine road, not in use, bears NE. and SW.