DEPENDENT RESURVEY OF PORTION OF THE SUBDIVISION OF T. 17 N., R. 21 E.

Chains	
	Survey commenced August 28, 1941 and surveyed in conjunction with resurveys in T. 18 N., R. 21 E. For description and tests of instruments, methods of measurement, and other technical data, refer to the field notes of resurveys in T. 18 N., R. 21 E., executed under this same group.
	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF T17N R21E Reestablishment of surveys executed by R.R.W.Norris, Deputy Surveyor, in 1867 under Contract No. 2.
	The original cor. of secs, 3, 4, 9 and 10 is a basalt rock, 16 x 10 x 6 ins., mkd. 5 notches on S. edge, 3 notches on E. edge, firmly set in an old mound of stone. At point for cor., in center of mound, Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to solid rock, with the original corner stone deposited at the base, and in a large mound of stone 8 ft. diam at base to top of post, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd. T17N R21E S 4 | S 3 S 9 | S 10 1941 from which, A juniper, 6 ins. diam., bears N.20°E., 518 lks. dist., mkd T17N R21E S3 BT A juniper, 7 ins. diam., bears S.80¼°E., 335 lks. dist., mkd T17N R21E S10 BT A juniper, 7 ins. diam., bears S. 1¼°W., 255 lks. dist., mkd T17N R21E S9 BT A pinon pine, 6 ins. diam., bears N.27 3/4°W., 325 lks. dist., mkd S4 BT U. S. C. & G. station "Geiger" bears S. 62° 57' W. Thence N. 1° 29' E., bet. secs. 3 and 4, (South half mile.) Over mountainous land thru medium dense low undergrowth and scattering timber. Asc. 185 ft. over rocky S. slope.
25.70	Rocky knoll; desc. 170 ft. over broken rocky NW. slope.
39.00	Head of shallow draw at SE. end of flat basin, drains E., asc. gentle S. slope.
40.40	The original ¼ sec. cor. of secs. 3 and 4 which is an old embedded mound of stones of comparable appearance and condition as other identified monuments of the same survey. No marked rock found. At point for cor., in center of mound, Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground,