

## DEPENDENT RESURVEY OF PORTION OF SUBDIVISION OF T. 18 N., R. 21 E.

Chains

from which,

A trapstone ledge, showing 5 x 4 x 4 ft. high, mkd B0 x 36 on top surface, bears S.  $45\frac{1}{2}^{\circ}$  E., 24 lks. distant.

A pinon pine, 8 ins. diam., bears S.  $60\frac{1}{2}^{\circ}$  W., 78 lks. dist., mkd  $\frac{1}{4}$  S35 BT

Thence

N.  $0^{\circ}$   $34'$  E., bet. secs. 35 and 36, (North half mile.)

Asc. 110 ft. over rocky SE. slope with timber gradually becoming more dense.

6.00 Slope changes to a gradual E. slope.

13.20 Rounded spur, slopes E., desc. 200 ft. over abrupt NE. slope thru very heavy second-growth timber.

32.00 Small draw, drains E., asc. 170 ft. over abrupt, rocky S. slope.

40.62 The original cor. of secs. 25, 26, 35 and 36, which is a basalt rock, 15 x 8 x 6 ins., mkd. 1 notch on E. and S. edges, firmly set in a mound of stone.

At point for cor., in center of mound,

Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to solid rock, with the original corner stone deposited at the base, and in a large mound of stone to top, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

T18N	R21E
S 26	S 25
S 35	S 36

1941

from which,

A pinon pine, 4 ins. diam., bears N.  $45\frac{1}{2}^{\circ}$  E., 180 lks. dist., mkd T18N R21E S25 BT

A basalt boulder, showing 4 x 4 x 4 ft. high, mkd. B0 x S36 near top of NW. face, bears S.  $37^{\circ}51'$  E., 107 lks. dist.

A juniper, 6 ins. diam., bears S.  $45\frac{1}{2}^{\circ}$  W., 184 lks. dist., mkd T18N R21E S35 BT

A pinon pine, 7 ins. diam., bears N.  $82\frac{1}{4}^{\circ}$  W., 102 lks. dist., mkd T18N R21E S26 BT

This corner is situated on gentle rocky E. slope at north edge or top of abrupt S. slope.

Land, mountainous; S.  $\frac{1}{4}$  mile, rolling bottom lands.  
Soil, sandy to gravelly loam, 2nd and 3rd rate with much surface rock on S.  $\frac{1}{4}$  mile; balance of mile, very rocky, 3rd and 4th rate.  
Timber, pinon pine, juniper.  
Undergrowth, sagebrush, buckbrush.  
Grazing, fair to good.

The original cor. of secs. 25 and 36 on the E. bdy. of the Tp., as established by W.A. Pray, U S Transitman in 1911 under Group No. 2, is a sandstone, 22 x 16 x 4 ins., firmly set in a mound of stone, and marked as described in the official record; field notes of the