

2218

Dependent Resurvey of the East Boundary of
T. 40 N., R. 24 E.

Chains

Dependent Resurvey of the East Boundary of
T. 40 N., R. 24 E.

Reestablishment of surveys executed by G. W. Garside,
Deputy Surveyor, in 1873.

Beginning at the cor. of Tps. 39 and 40 N., Rs. 24 and 25 E., which is limestone, 5 x 8 x 17 ins., showing 3 ins. above the surface, firmly set, mkd. with 6 grooves on N., S., E. and W. faces; alongside of which, firmly set, is a steel shaft 1 inch diam., showing $1\frac{1}{2}$ ft. out of ground, and with many decayed pieces of cedar and cottonwood around.

At point for the corner, with the original corner monument and steel shaft buried alongside,

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 40 N	
R24E	R25E
S36	S31
S 1	S 6
T 39 N	
1942	

raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

Thence

N. $0^{\circ} 53'$ E., bet. secs. 31 and 36.

Over rolling land, through dense undergrowth, desc. gradually.

- | | |
|-------|---------------------------------------------------------------------------------------------------------------------------------------------|
| 2.60 | Shallow wash, 5 lks. wide, course N. 60° E. |
| 10.60 | Shallow wash, 5 lks. wide, course N. 60° E. |
| 14.20 | Wire fence, bears N. 40° E. and S. 40° W. |
| 17.00 | Point of shoulder of low spur, slopes E. |
| 25.80 | Edge of meadow, bears E. and W. |
| 35.40 | Wire fence, bears N. 30° W. and SE. |
| 41.15 | Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner. |
| | Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. |

$\frac{1}{4}$	
S36	S31
1942	

dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.