

Dependent Resurvey of the East Bdy. of T. 40 N., R. 24 E.

Chains

$$\left| \frac{1}{4} \text{ S } 6 \right.$$

1942

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

44.20 Top of broad spur, 10 ft. above $\frac{1}{4}$ sec. cor., slopes S. 60° W.; ascend 160 ft.

82.72 The closing cor. of T. 40 N., Rs. 24 and 25 E., marked by the original monument, a lava stone, 12x9x6 ins., firmly imbedded in a small mound of stone, mkd. 6 grooves on S. and E. and W. faces.

At the corner point, with the original corner monument deposited at the base.

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, with brass cap mkd.

S 1	S 6
R24E	R25E
T 40 N	
CC	

1942

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of corner.

Land, rolling mountainous.

Soil, sandy clay loam, gravelly and rocky; 3rd and 4th rate.

Timber, none; undergrowth, sagebrush, greasewood, shade-scale and a fair growth of grass.

Dependent Resurvey of a Portion of the South Boundary
of T. 40 N., R. 25 E.

Reestablishment of surveys executed by G. W. Garside,
Deputy Surveyor, in 1873

From the cor. of Tps. 39 and 40 N., Rs. 24 and 25 E.,
S. $89^\circ 48'$ E., bet. secs. 6 and 31.

Over rolling land, through dense undergrowth.

35.50 Wire fence, bears N. and extends S. 70 lks. to fence corner; whence fence bears N. 89° E.

40.25 The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, marked by the original monument, a granite stone, 20x16x5 ins., firmly set in a large mound of stone, mkd. $\frac{1}{4}$ on N. face.

This cor. is located 16 lks. N. of the cor. of wire fences; from which fences bear N. and S. 89° W.

At the cor. point, with the original corner stone buried alongside.