## DEPENDENT RESURVEY, N. BDY., T. 39 N., R. 24 E.

	Chains	
		Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.
		½ S31
85 20 10		1946
		raise a mound of stone, 2 ft. base, $l_{\mathbb{Z}}^{\frac{1}{2}}$ ft. high, N. of corner.
	30.20	Desc. 70 ft. over W. slope.
	38.50	Intermittent stream, trickle of water at this point, flows S.; asc. 30 ft. to 4 sec. cor.
	42.52	The # sec. cor. of secs. 6 and 31, marked by the original monument, a rough granite stone, 7x13x16 ins., firmly set in the ground and in an old imbedded mound of stone.  No marks could be found on the stone. This corner is changed to the # sec. cor. of sec. 6 only.
		At the corner point
	2 1	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, with a lava stone 8x5x3 ins., mkd. X, deposited at the base and in a mound of stone to top, with brass cap mkd.
4		
1 1		1946
	w .	
		S. 66° 53' W., beginning new measurement.
		Descend slightly over rolling land.
	7.30	Wash, course SE.; asc. 50 ft. over general E. slope.
	13.05	The corner of Tps. 39 and 40 N., Rs. 23 and 24 E., marked by the 1914 resurvey monument, an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.
	W N	Land, rolling. Soil, gravelly and rocky; 3rd rate. Timber, none. Undergrowth, sagebrush. Grazing, fair.
		Dependent Resurvey of the East Boundary of T. 40 N., R. 23 E. (Sec. 36 only)
		This dependent resurvey is made only for the purpose of changing the established corners of minimum control to corners of maximum control and consists only of changing the markings on the iron posts. The bearings and distances are those reported in the resurvey executed in 1918 under Group No. 48, Nevada. Reference should be made to the record of the 1918 resurvey for items of topography; description of corner monuments and other