

271

DEPENDENT RESURVEY, E. BDY., T. 40 N., R. 23 E.

Chains	detail not reported here.
	North, bet. secs. 31 and 36.
41.12	The $\frac{1}{4}$ sec. cor. of sec. 36 only, which is changed to the $\frac{1}{4}$ sec. cor. of secs. 31 and 36. The brass cap is remarked $\frac{1}{4}$ S36 S31 1918
81.12	The cor. of secs. 25 and 36 only, which is changed to the cor. of secs. 25, 30, 31 and 36. The brass cap is remarked T40N R23E R24E S25 S30 S36 S31 1918

Dependent Resurvey of a Portion of the Subdivision of
T. 40 N., R. 24 E.

Reestablishment of the Survey Executed by G. W. Garside,
Deputy Surveyor, in 1873.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy.
of the township.

N. $1^{\circ} 03'$ E., bet. secs. 35 and 36.

Over slightly rolling land draining generally NE. to E.

42.56 The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, marked by the
original monument, a granite stone, 5x7x12 ins., mkd.
 $\frac{1}{4}$ on E. face, set in an old imbedded mound of stone.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, with the original marked stone deposited at
the base, with brass cap mkd.

$\frac{1}{4}$
S35 | S36
1946

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of
corner.

N. $0^{\circ} 52'$ E., beginning new measurement.

Over slightly rolling bench land draining E.

6.30 Descend 50 ft. over N. slope.