

DEPENDENT RESURVEY, PORTION OF THE SUBDIVISION
of T. 40 N., R. 24 E.

Chains 8.60	Dry channel, 20 lks. wide, 2 ft. deep, course S. 20° E.
41.66	The cor. of secs. 13, 14, 23 and 24. Land, rolling. Soil, gravelly and rocky; 3rd rate. Timber, none. Undergrowth, shadscale and sagebrush. Grazing, fair.
	Subdivision of a Portion of T. 40 N., R. 24 E., M.D.M.
	Extension of the survey of the subdivision lines. From the cor. of secs. 33 and 34, on the S. bdy. of the Tp. North, along sectional guide meridian, bet. secs. 33 and 34. Descend 30 ft. over N. slope.
2.50	S. side of gorge, 100 ft. deep, course N. 60° E.
4.00	N. side of gorge; ascend 50 ft. over SE. slope, changing to E. slope.
11.00	Desc. 70 ft. along E. slope changing to NE. slope.
31.70	Draw, drains S. 70° E.; ascend 40 ft. over gradual SE. slope.
36.70	Dim road, bears irregularly S. 75° E. and N. 85° W.
36.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, 40.00 chs. S. of the corner of secs. 27, 28, 33 and 34. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to underlying rock, with a lava stone, 2x4x8 ins., mkd. X, deposited at the base, and in a mound of stone to top, with brass cap mkd.
	$\frac{1}{4}$ S33 S34 1946
40.00	Along E. slope.
45.00	Desc. 50 ft. along E. slope, changing to NE. slope.
64.40	Unimproved road, bears S. 35° W. and N. 35° E., curving to N. 60° E.
66.20	Wash, course NE.; desc. 30 ft. to sec. cor.
76.95	Point for the cor. of secs. 27, 28, 33 and 34, at the intersection with the governing section line. Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to underlying rock, with a lava stone, 2x6x8 ins., mkd. X, deposited at the base, and in a mound of stone to top, with brass cap mkd.