

Dependent Resurvey of a Portion of the Eighth Standard Parallel North,  
through R. 25 E.

Chains	S. 85° 53' E., along the S. bdy. of sec. 36.
	Asc. gradually.
4.00	Asc. 250 ft. over W. slope.
8.80	Top of ledge, 85 ft. high, extends N. and S.
13.00	Across top of spur, projects N. 10° E. for 5 chains.
14.50	Desc. 150 ft. over rocky E. slope.
22.00	Desc. slightly across bench.
30.20	Ravine, course N.; asc. slightly.
42.54	Point for the standard $\frac{1}{2}$ sec. cor. of sec. 36 at proportionate distance; there is no remaining evidence of the original corner.
	Although the field record omits any reference to the description of this corner, a memorandum in the files dated September 30, 1947 indicates this point was monumented, probably with an iron post.
	Continue across bench.
59.00	Top of the W. side of canyon through which White Rock Creek flows northerly.
	Distance to the standard township corner on the top of the east side of the canyon was determined by triangulation.
85.08	The standard cor. of Ts. 40 N., Rs. 25 and 26 E., mkd. by an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record.
	Land, bench land and mountainous.
	Soil, gravelly and rocky, 3rd and 4th rate.
	Timber, none; undergrowth, sagebrush.
Survey of the East 4 Miles of the S. Bdy. of T. 40 N., R. 25 E.	
	From the cor. of secs. 4, 5, 32 and 33, Ts. 39 and 40 N., R. 25 E., mkd. by an iron post, 2 ins. diam., described in the approved field notes of the 1942 resurvey.
	East, along the S. bdy. of sec. 33.
	Asc. 30 ft. over valley floor.
5.00	Asc. 650 ft. over steep, rocky W. slope.
20.80	Minor spur, slopes steeply NW.; desc. 35 ft. over NE. slope.
23.20	Head of ravine, course NW.; asc. 350 ft. over steep, rocky W. slope, changing to general SW. slope.
37.78	Point for the cor. of lots 11 and 12, on the S. bdy. of sec. 33.
	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to underlying rock, and in a mound of stone to top, with brass cap mkd.