

Survey of the East 4 Miles of the S. Bdy. of T. 40 N., R. 25 E.

Chains

T40N	R25E
S35	S36

1946

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

This cor. is situated in a draw draining N. 85° E.

Land, rough, mountainous and rolling.

Soil, gravelly and rocky, 2nd and 4th rate.

Timber, none; undergrowth, sagebrush.

East, along the S. bdy. of sec. 36.

Asc. 60 ft. along gradual N. slope.

15.00 Desc. 70 ft. along gradual N. slope.

40.00 Point for the ¼ sec. cor. of sec. 36.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

¼	S	36
---	---	----

1946

Deposit a lava stone, 1½x3x4 ins., mkd. with a cross (X), at base of the iron post.

Desc. 30 ft.

80.00 Intersect the W. bdy. of sec. 6, T. 39 N., R. 26 E.

Point for the closing corner of Ts. 39 and 40 N., R. 25 E.

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, with brass cap mkd.

T40N		
R25E		T39N
S36		R26E
CC—		S6
S1		
T39N		

1946

From which the cor. of Ts. 39 and 40 N., R. 26 E., bears North, 4.49 chs. dist. This corner, monumented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record, now becomes the corner of Ts. 39 and 40 N., R. 26 E. only and the brass cap is remarked:

T40N		
R25E		R26E
S36		S31
		R26E
		S6
		T39N

1910

From the closing corner, the ¼ sec. cor. on the E. bdy. of sec. 1 bears South, 65.10 chs. dist., monumented with an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record.