

Dependent Resurvey of the West Boundary, T. 26 N., R. 49 E.

Chains	
	N. 0° 31' W., along the W. bdy. of sec. 18.
	Asc. 60 ft. over open, rocky SE. slope, through scattered undergrowth.
24.10	Bottom of small canyon, drains SE.; asc. 80 ft. over S. slope.
40.02	Point for the ¼ sec. cor. of sec. 18, at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T26N R49E   ¼   S18 1957
	from which
	The original ¼ sec. cor. of sec. 12, T. 26 N., R. 48 E., a granite stone, set, mkd. and witnessed as described in the official record of the 1869 survey by Hatch and Eaton, bears N. 89° 45' W., 1.24 chs. dist. I destroy all evidence of this corner.
	Asc. 85 ft. over rolling, broken general SE. slope to cor. point.
49.00	Bottom of small canyon, drains SE.
70.50	Point of spur, slopes SE.
75.00	A spring, bears E. about 10 chs. dist.
78.60	Bottom of small canyon, drains SE.
80.04	Point for the cor. of secs. 7 and 18 at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 5 ft. base to top, with brass cap mkd.
	T26N R49E   S 7   S18 1957
	from which
	The original corner of sec. 1 and 12, T. 26 N., R. 48 E., which is a trapstone, set, mkd. and witnessed as described in the official record of the survey of the E. bdy., T. 26 N., R. 48 E. by Hatch and Eaton in 1869, bears S. 71° 50' W., 71 lks. dist. I destroy all evidence of this corner.
	Land, open, rolling hills, general SE. drainage.
	Soil, rocky.
	Timber, none.
	Undergrowth, brush and sagebrush.
	N. 0° 31' W., along the W. bdy. of sec. 7.
	Asc. 150 ft. over rocky, broken SE. slope, through heavy sagebrush.
0.40	Wash, 10 lks. wide, 1 ft. deep, drains SSE.