1) 111

	•- (•	Dependent Resurvey of the West Boundary, T. 26 N., R. 49 E.
	Chains	
,	21.00	Point of spur, slopes SE.; desc. 60 ft. over NE. slope.
	23.20	Top of lava ledge, 20 ft. high, bears NW. and SE.
	31.00	Head of draw, drains SE.; asc. 30 ft. over SE. slope.
	40.02	Point for the ½ sec. cor. of sec. 7; there is no remaining evidence of the original corner.
	e land	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	c *	T26N R49E.
×	e *	Continue ascent; asc. 20 ft. over SE. slope.
	45.00	Crest of spur, slopes NE.; desc. 70 ft. over N. slope.
	55.10	Bottom of canyon, drains E.; asc. 75 ft. over rolling, broken general SE. slope.
	59.00	Point of spur, slopes E.
	61.00	Bottom of gulch, drains SE.
ic i	66.10	Point of spur, slopes SE.
	78.50	Gulch, drains SE.
	80.04	The original corner of secs. 6 and 7, which is monumented with a granite stone, 15x9x8 ins., with 5 notches on one side, 1 notch on the opposite side, set loosely in the ground,
	- 3	At the corner point
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins.diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
		$ \begin{array}{c} $
		1957
· ·		Bury original corner stone alongside iron post.
10.1		from which
		The original cor. of Ts. 26 and 27 N., R. 48 E., a granite stone, 10x12x24 ins., set in a mound of stone and mkd. with 6 notches on N., S. and W. edges, bears S., 1.08 chs. dist. I destroy all evidence of this corner.
4.	27. 2	Note: The W. bdy. of sec. 6 was retraced N. of the cor. of secs. 6 and 7. No evidence was found of the original cors. along this bdy.
		Independent Resurvey of a Portion of the N. Bdy., T. 26 N., R. 48 E.
	• 40 000	The point for the original cor. of secs. 2, 3, 34 and 35 on the N. bdy of the township is reestablished at proportionate position; there is no remaining evidence of the original corner. This corner now functions for secs. 2 and 3 only.