

Independent Resurvey of a Portion of the N. Bdy., T. 26 N., R. 48 E.

Chains 40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 1, which is 40.00 chs. E. of the calculated position of the cor. of secs. 1 and 2.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 3 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T27N R48E $\frac{1}{4}$ S 1 T26N 1957</p> <hr style="width: 20%; margin: auto;"/> <p>East, beginning new measurement.</p> <p>Continue descent, desc. 335 ft. over broken general ESE. slope.</p>
11.00	Draw, drains SE.
42.15	<p>Intersect the W. bdy. of sec. 6, T. 26 N., R. 49 E.</p> <p>Point for the closing cor. of Ts. 26 and 27 N., R. 48 E.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T27N R48E T26N C S36 R49E C S 1 S 6 T26N 1957</p> <p>From this point, the cor. of secs. 6 and 7, T. 26 N., R. 49 E., hereinafter described, bears S., 2.21 chs. dist.</p> <p>Land, mountainous. Soil, rocky. Timber, none. Undergrowth, sagebrush.</p>
Survey of a Portion of the Subdivision, T. 26 N., R. 48 E.	
7.10	<p>Beginning at the standard corner of secs. 35 and 36, which is a 2 in. iron post, set, mkd. and witnessed as described in the official record of the 1922 resurvey of the 5th Standard Parallel North, through R. 48 E.</p> <p>North, bet. secs. 35 and 36.</p> <p>Over gently rolling land, through scattered timber and sagebrush.</p> <p>Desc. 45 ft. over general E. slope.</p>
16.00	Wash, 25 lks. wide, 2 ft. deep, drains NE.
16.50	Dirt road, bears NE. and SW.
37.30	Wash, 10 lks. wide, 1 ft. deep, drains E.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>