

Survey of a Portion of the Subdivision, T. 26 N., R. 48 E.

Chains	T26N R48E S25 1/4 S36 1957 from which A juniper, 6 ins. diam., bears S. 34° W., 1.37 chs. dist., mkd. 1/4 S36 BT. A juniper, 8 ins. diam., bears N. 32 1/2° E., 1.04 chs. dist., mkd. 1/4 S25 BT. Continue descent, desc. 165 ft. over broken, general NE. slope. 47.90Bottom of swale, drains NE. 80.00Point for the 1/16 sec. cor. of secs. 25 and 36. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. T26N R48E S25 1/16 S36 80 1957 85.80Intersect W. bdy. of sec. 31, T. 26 N., R. 49 E. Point for the closing cor. of secs. 25 and 36. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. T26N R48E R49E S25 C S36 S31 1957 From this point, the SW. cor. of T. 26 N., R. 49 E., hereinbefore described, bears S. 0° 31' E., 7.66 chs. dist. Land, rolling foothills. Soil, sandy loam. Timber, thinly scattered juniper. Undergrowth, sagebrush.
	From the cor. of secs. 25, 26, 35 and 36. North, bet. secs. 25 and 26. Over rolling hills, general SE. drainage, through scattered timber and sagebrush. Asc. 170 ft. over broken SE. slope. 2.30Wash, 10 lks. wide, 3 ft. deep, drains E. 4.70Point of spur, slopes E. 6.80Wash, 20 lks. wide, 6 ft. deep, drains SE. 11.30Wash, 30 lks. wide, 2 ft. deep, drains SE. 29.50Three strand barbed wire fence on cedar posts, bears SE. and NW. 37.60Point of spur, slopes S., 2.00 chs., thence SE.