

Survey of a Portion of the Subdivision, T. 26 N., R. 48 E.

Chains	
24.00	Point of spur, slopes SE.
34.80	Wash, 10 lks. wide, 3 ft. deep, drains SSE.; asc. 50 ft. over SW. slope to point for $\frac{1}{4}$ sec. cor.
39.10	Head of draw, drains SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T26N R48E $\frac{1}{4}$ $\frac{S24}{S25}$ 1957 from which A juniper, 7 ins. diam., bears N. $22\frac{1}{2}^\circ$ W., 21 lks. dist., mkd. $\frac{1}{4}$ S24 BT. A juniper, 10 ins. diam., bears S. 21° E., 43 lks. dist., mkd. $\frac{1}{4}$ S25 BT. Continue ascent, asc. 60 ft. over SW. slope.
43.90	Point of spur, slopes SW.
48.40	Crest of spur, slopes S. about 4.00 chs., thence ESE.; desc. 220 ft. over S. slope.
74.40	Old fence line, bears NE. and SW.
80.00	Point for $\frac{1}{16}$ sec. cor. of secs. 24 and 25. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T26N R48E $\frac{1}{16}$ $\frac{S24}{S25}$ 80 1957 from which A juniper, 8 ins. diam., bears N. 65° E., 25 lks. dist., mkd. $\frac{1}{16}$ S24 80.00 BT. A juniper, 7 ins. diam., bears S. 59° W., 1.54 chs. dist., mkd. $\frac{1}{16}$ S25 80.00 BT.
85.10	Intersect the W. bdy. of sec. 30, T. 26 N., R. 49 E. Point for the closing cor. of secs. 24 and 25. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T26N R48E R49E C $\frac{S24}{S25}$ S30 1957 Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. From this point, the cor. of secs. 30 and 31, T. 26 N., R. 49 E., hereinbefore described, bears S. $0^\circ 31'$ E., 7.60 chs. dist.