

328

Survey of a Portion of the Subdivision, T. 26 N., R. 48 E.

Chains	
65.40	Top of lava flow, 50 ft. high, bears NNW. and SSE.
83.55	Intersect W. bdy. of sec, 18, T, 26 N., R. 49 E. Point for the closing cor. of secs, 12 and 13. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T26N R48E R49E C S12 S18 C S13 1957 From this point, the cor. of secs. 7 and 18, T. 26 N., R. 49 E., here- inbefore described, bears S. 0° 31' E., 7.50 chs. dist. Land, rolling hills. Soil, rocky. Timber, W. ½ scattered juniper and pinion, E. ½ none. Undergrowth, sagebrush.
	From the cor. of secs. 11, 12, 13 and 14. North, bet. secs. 11 and 12. Over semi-mountainous land, through scattered timber.
6.20	Draw, drains SW.; asc. 420 ft. over general S. slope to point for ¼ sec. cor.
27.80	Spring, flowing SSW., bears E., 20 lks. dist.
40.00	Point for the ¼ sec. cor. of secs. 11 and 12. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T26N R48E ¼ S11 S12 1957 Continue ascent; asc. 290 ft. over broken, general SSE. slope.
44.00	Lava rimrock, 15 ft. high, bears NW. and SE., leave timber.
70.70	Point of spur, slopes SE.
80.00	Point for the cor. of secs. 1, 2, 11 and 12. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, over a cross (X) on rock, with brass cap mkd. T26N R48E S 2 S 1 S11 S12 1957 Land, rolling hills, general SE. drainage. Soil, rocky. Timber, S. ½ scattered juniper and pinion, N. ½ none. Undergrowth, sagebrush.