

Dependent Resurvey of the South Boundary of
T. 34 N., R. 62 E.

13

Chains

Dependent Resurvey of the South Boundary of
T. 34 N., R. 62 E.

Reestablishment of surveys executed by
Hatch and Eaton, Deputy Surveyors in
1870

From the cor. of Tps. 33 and 34 N., Rs. 61 and 62 E.

N. 89° 39' E., bet. sec. 6 and 31. (W. $\frac{1}{2}$ mile.)

Over nearly level brush land.

- 6.60 Center of oiled highway, bears N. 22° 15' E. and S. 22° 15' W.
- 10.70 Old road, not graded, bears N. 15° E. and S. 15° W.
- 19.10 Edge of gravel pit, extends N. and S., for 5.00 chs.
- 30.10 Edge of gravel pit, extends N. for about 5.00 chs. and S. for about 2.00 chs.
- 40.13 The original $\frac{1}{4}$ sec. cor., a juniper stake 40 ins. long, 2 ins. diam., partly decayed, mkd. $\frac{1}{4}$ S 31 on N. side.

At point for corner

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with glass bottles and the original stake deposited at base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S31}{S6}$$

1942

No suitable accessory.

Thence

N. 89° 46' E., bet. secs. 6 and 31. (E. $\frac{1}{2}$ mile.)

Over nearly level land.

- 37.30 Fence, bears N. and S.

- 39.16 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with a glass bottle deposited at base, for cor. of secs. 5, 6, 31 and 32, with brass cap mkd.

$$\begin{array}{cc} T34N & R62E \\ S31 & | & S32 \end{array}$$

$$\begin{array}{cc} S6 & | & S5 \end{array}$$

T33N

1942

18x18x12 ins., in each sec., 3 ft. dist. dig pits,

Land, level.

Soil, light sandy loam, free from rocks; 3rd rate.

No timber.

Undergrowth, sagebrush, greasewood and a fair growth of grass.