41

Dependent Resurvey of the Subdivision of T. 35 N., R. 62 E.

Chains	Thence
	N. 0° 12' W., bet. secs. 3 and 4. (N. \frac{1}{2} mile.)
•	Over nearly level land.
10.50	Dim road, bears N. 80° W. and S. 80° E.
18.30	Old graded road, bears N. 80° E. and S. 80° W.
27.80	Dim road, bears NE. and SW.
40.05	The original closing cor. of secs. 3 and 4, a very old and badly weathered cottonwood post, 3 ins. diam., 40 ins. long, squared on two faces, fallen beside a more recently set stake.
	At original corner point.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original post deposited at base, and with brass cap mkd.
	W P
	· 1943
40.34	Intersect the Seventh Standard Parallel North.
ξ ,	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a granite stone, 5x5x3 ins., mkd. with a cross (X), deposited at the base, for closing cor. of secs. 3 and 4, with brass cap mkd.
a	T36N R62E S 33 S4 S3 T35N R62E CC
,	1942 raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.
	From the closing sec. cor., the standard cor. of secs 33 and 34, an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record, bears N. 89° 13' E., 20.00 chs. dist.
•	From the closing sec. cor., the standard \(\frac{1}{4} \) sec. cor., bears S. 89° 13' W., 20.07 chs. dist.
	Land, nearly level. Soil, clay and clay loam; 2nd to 4th rate. No timber; undergrowth, greasewood, sagebrush and rabbitbrush. Grazing, poor to good.
e e	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the township, an iron post, 2 ins. diam., described in the field notes of the Resurvey of T. 34 N., R. 62 E., executed under this same group.
	N: 0° 22' W., bet: secs. 32 and 33.

Over nearly level land.