

Dependent Resurvey, Ruby Valley Guide Meridian, Through T. 21 N.,
Between Rs. 55 and 56 E.

Chains	N. 0° 05' E., bet. secs. 1 and 6. Over bed of Alkali Lake.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ S 1 S 6 \\ 1941 \end{array}$
	No suitable accessory.
68.00	Shore of Alkali Lake, bears W. and NE.; thence over low-lying, but dry sandy land.
79.98	The cor. of Ts. 21 and 22 N., Rs. 55 and 56 E., which is monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the field notes of the dependent resurvey of the Ruby Valley Guide Meridian through T. 22 N., bet. Rs. 55 and 56 E., executed concurrently under Group 281. Land, level. Soil, sandy clay, part inundated during spring runoff. No timber; undergrowth, none.

Dependent Resurvey of the Fourth Standard Parallel North, Along a
Portion of the South Boundary of T. 21 N., R. 55 E.

Reestablishment of the Survey Executed by
C. C. Tracy, Deputy Surveyor, in 1868.

	From the standard corner of Ts. 20 and 21 N., Rs. 55 and 56 E. S. 89° 48' W., along the S. bdy. of sec. 36, T. 21 N., R. 55 E. Over bed of Alkali Lake.
39.99	Point for the standard $\frac{1}{4}$ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd. $\begin{array}{c} S C \\ \frac{1}{4} S 36 \\ 1941 \end{array}$
	No suitable accessory.
79.98	Point for the standard cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd. $\begin{array}{c} S C \\ T 21 N R 55 E \\ S 35 S 36 \\ 1941 \end{array}$